



SPECIFICATIONS:
 SERVICE, PLANT AIR
 M.O.P., 150 PSI
MATERIALS:
 BODY, COVER & PISTON, ALUM ALLOY
 BODY & PISTON, HARD COATED
 SEALS, BUNA N O-RINGS
 BUSHINGS, OIL IMPREGNATED BRONZE

DIMENSIONS:
 BODY BORE, 2.340 in.
 EXT. PISTON AREA, 4.300 sq.in.
 RETR. PISTON AREA, 3.858 sq. in.
 ROD DIA., .375
 ROD THREAD, 1/2-13
 WRENCH FLATS, .625
 PORTS, 1/8 NPTF

FABRICATE TO MACHINING STANDARD MMS - 220
 COPYRIGHTED ENGINEERING DESIGN.

© 2002 MACK CORPORATION

MACK CORPORATION Flagstaff, AZ

SPECIFICATIONS ARE IN U.S. CUSTOMARY UNITS. BRACKETS INDICATE METRIC SPECIFICATIONS.
 SCALE: DR. DATE: 8/9/02
 HALF: FM: APPROV. DATE: TOOLING REFERENCE NUMBERS: PR-2 PRODUCT FIXTURES

LETR.	DATE	BY	REVISION	PART NAME	PART NUMBER	REV.
				L0-Profile® LINEAR ACTUATOR	74230	
				3.500 O.D. X 3.000 STROKE		